



Drill Shack

Features and Specifications

- 6.7 m L x 3 m W x 2.8 m H / 22 ft L x 10 ft W x 9 ft H
- Options:
 - Wall insulation
 - Rod handler / Rod rack
 - 4 x Leveling corner jacks
 - Heat exchanger for diesel engine (used as heating system)
 - Wheel set up



Get in touch with us to discuss our products [in](#) [f](#)
DrillcoMining.ca

Drillco Mining & Exploration
400-E Kirkpatrick Street,
North Bay, ON P1B 8G5 Canada
(705) 476-3629

Sylvain Brisson
President – Operations Director
Mobile (705) 622-2829
S.Brisson@DrillcoMining.ca

David Jones
Business Development Officer
Mobile (705) 492-7307
D.Jones@DrillcoMining.ca

Control Panel

Features and Specifications

- Rotation Speed Joystick with Speed Adjust Trigger Switch for manual Chuck option (c/w Gimbal Mount)
- Feed Cylinder Joystick with Trigger Switch for manual Rod Clamp option (c/w Gimbal Mount)
- Wireline Joystick
- Winch Joystick
- Adjustable Feed Pressure, Hold Back, and Water Pump Controls
- Comes with “High Pressure” Manifold (Bicycle) for Pressure Pump
- Weight: 100lbs / 45kg (incl. pedestal)



Driller's Settings

- Driller's Settings
- Dimmer Adjust for Screen Display
- RPM Meter (optional)
- Amp Meter
- Error Display
- Manual/Synchro Option
- Auxiliary On/Off
- Drilling Mode:
 - Rotation Speed Control Adjust
 - Torque Control
- Trip In/Out
 - Thread Making/Breaking Feed Cylinder Speed Adjust
 - Thread Making/Breaking Rotation Speed Adjust
 - Thread Making/Breaking Torque Adjust

Owner's Locked Settings

- Interlock On/Off
- Fast Feed: Max Feed Cylinder Flow and Pressure
- Drilling Mode:
 - Rotation Motor Displacement and Pressure Maximums
 - Feed Cylinder Flow and Pressure Maximums
- Trip In/Out
 - Thread Making/Breaking Feed Cylinder Speed Maximums
 - Thread Making/Breaking Rotation Speed Maximums
 - Thread Making/Breaking Torque Maximums
 - Synchro Delay