



## Production Long-Hole Drill

### Features and Specifications

- Radial Piston Air Motor      22KW      30HP
  - Piston Pump                    68 h/min   18 GPM
  - Main Reservoir                38 Liters   10 Gallons
  - Oil Lubricator                 9 Liters    2 Gallons
- Min Requirements to Drill
  - Air Flow at 90 PSI            16 m3/min – 575 CFM
  - Water Flow                     38 h/min – 10 GPM
- Gradeability – 30%
  - 4 Wheel Independent Drive & Braking
  - Solid Rubber Tires on Steel Rims
  - Quick Disconnect Brakes for Easy Towing
  - Motion Control Valve for Precise Control
- Dump + 25° +- 180° Via Hydraulic Slewing Ring
- Travers Side to Side
  - 1.219m      48”
  - 1.524m      60”
  - 1.829m      72”
- Adjustable Pads to Compensate for Wear Movement Via Hydraulic Cylinder Rotation Via Hydraulic Slewing Ring 360°
- 536 Rock Drill
- Exhaust Inside Drill for Better Noise Reduction
- Hydraulic Drill
  - High Efficiency Electric Motor      56KW – 75HP
  - Load Sensing Piston Pump
  - Nema 4 Electric Panel
- Rock Drill HC109 Montabert



Get in touch with us to discuss our products [in](#) [f](#)

[DrillcoMining.ca](http://DrillcoMining.ca)

#### Drillco Mining & Exploration

400-E Kirkpatrick Street,  
North Bay, ON P1B 8G5 Canada  
(705) 476-3629

#### Sylvain Brisson

President – Operations Director  
Mobile (705) 622-2829  
S.Brisson@DrillcoMining.ca

#### David Jones

Business Development Officer  
Mobile (705) 492-7307  
D.Jones@DrillcoMining.ca